

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

Selected Sections: 01602 Equipment Rental, 05100 Structural Metal Framing, 06100 Rough Carpentry, 07210 Building Insulation, 07920 Joint Sealants, 08110 Access Doors, 09221 Non Structural Metal Framing, 09290 Drywall

Selected Typical Areas:

Selected Areas: (unassigned), CEILING (AREA A, AREA B, AREA C), WALLS (AREA A, AREA B, AREA C), ROOF

Estimator: **BR - Barry Ricketts**

Job Status: **Pending**

Job Class: **Commercial**

Bid Date/Time: **4/27/2010 12:00:00 PM**

Wage Type: **Open**

Plans Date: **3/29/2010**

Job Site: Children's Reading Center & Museum, SR 84 & SW 121st Avenue, Davie, FL 33314

**01602 Equipment Rental
CEILING**

Equipment	Quantity	Total Price	Man Days
Man Lift	3.00 Mo.	8,426.25	0.00
Equipment & Labor Total:		8,426.25	0.00
CEILING Total:		8,426.25	0.00

WALLS

Equipment	Quantity	Total Price	Man Days
Man Lift	5.00 Mo.	14,043.75	0.00
Equipment & Labor Total:		14,043.75	0.00
WALLS Total:		14,043.75	0.00
01602 Equipment Rental Total:		22,470.00	0.00

**05100 Structural Metal Framing
CEILING\AREA A**

No.	Condition	Height	Quantity	Man Days
1	DETAIL 1/A50201(ACP-1) 2X4 SUSPENDED ACT CEILING 4" MAIN CARRIER STUD ATTACHED TO WALL 32" OC, ACOUSTICAL BATT INSULATION OVER ACP CEILING, WHERE REQUESTED		3,932.02 SF	14.97
70	DETAIL 1/A50201(ACP-1) 2X4 SUSPENDED ACT CEILING 4" MAIN CARRIER STUD ATTACHED TO WALL		1,247.71 SF	4.75
Material & Labor Total:			10,204.36	19.72
CEILING\AREA A Total:			10,204.36	19.72

CEILING\AREA B

No.	Condition	Height	Quantity	Man Days
1	DETAIL 1/A50201(ACP-1) 2X4 SUSPENDED ACT CEILING 4" MAIN CARRIER STUD ATTACHED TO WALL 32" OC, ACOUSTICAL BATT INSULATION OVER ACP CEILING, WHERE REQUESTED		2,884.09 SF	10.98
2	DETAIL 1/A50201 (ACP-2) 2X4 SUSPENDED ACT CEILING 4" MAIN CARRIER STUD ATTACHED TO WALL 32" OC, ACOUSTICAL BATT INSULATION OVER ACP CEILING, WHERE REQUESTED.		432.76 SF	1.65
70	DETAIL 1/A50201(ACP-1) 2X4 SUSPENDED ACT CEILING 4" MAIN CARRIER STUD ATTACHED TO WALL		673.97 SF	2.57
Material & Labor Total:			7,862.27	15.20
CEILING\AREA B Total:			7,862.27	15.20

CEILING\AREA C

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

05100 Structural Metal Framing

CEILING\AREA C

No.	Condition	Height	Quantity	Man Days
1	DETAIL 1/A50201(ACP-1) 2X4 SUSPENDED ACT CEILING 4" MAIN CARRIER STUD ATTACHED TO WALL 32" OC, ACOUSTICAL BATT INSULATION OVER ACP CEILING, WHERE REQUESTED		2,747.07 SF	10.46
Material & Labor Total:				10.46
CEILING\AREA C Total:				10.46

WALLS\AREA A

No.	Condition	Height	Quantity	Man Days
13	WALL TYPE 09 CONTINUOUS SEALANT 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS 8" STL, STUD (18 GA) @12" O.C. 3/4" FIRE PETARDANT TREATED PLYWOOD BD, ATTACHED TO STL, STUD W/COUNTER SUNK SCREWS (EXTEND PLYWOOD TO 12'-0" AFF AT EXHIBIT AREAS)	22' 0"	140.90 LF	13.33
14	WALL TYPE 10 CONTINUOUS SEALANT TOP AND BOTTOM EACH SIDE 5/8" GYPSUM WALLBOARD TO UNDERSIDE OF DECK, TAPE AND SPACKLE ALL JOINTS 8" STL, STUD (18 GA @ 12" O.C.	24' 0"	22.82 LF	3.79
17	WALL TYPE 13	14' 0"	106.76 LF	10.40
21	WALL TYPE 09	24' 0"	33.53 LF	4.74
22	WALL TYPE 11 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16" O.C. DASHED LINE DENOTES STRUCTUPAL STL, TUBE CONCEALED W/I RARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A.) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES	14' 0"	294.32 LF	24.41
29	WALL TYPE 12 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBORAD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	229.04 LF	20.66
39	WALL TYPE 13 - W/ NO INSULATION NO INSULATION IS INCLUDED IN THIS CONDITION PER WALL TYPE SCHEDULE	13' 0"	33.69 LF	3.07
41	WALL TYPE 13 - CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET; 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE, ADD 2" THICK FOAM ACOUSTIC TREATMENT APPLIED FULL HIGHT TO WALL SURFACES IN ROOMS 1006A AND 1006B ONLY	12' 0"	62.75 LF	5.33
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET; 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	153.14 LF	13.02
47	WALL TYPE 11- W/ TILE BACKER	14' 0"	24.00 LF	2.12
Material & Labor Total:				100.88
WALLS\AREA A Total:				100.88

WALLS\AREA B

No.	Condition	Height	Quantity	Man Days
22	WALL TYPE 11 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16" O.C. DASHED LINE DENOTES STRUCTUPAL STL, TUBE CONCEALED W/I RARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A.) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES	14' 0"	47.50 LF	3.94
29	WALL TYPE 12 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBORAD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	24.33 LF	2.19
39	WALL TYPE 13 - W/ NO INSULATION	13' 0"	337.98 LF	30.84

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

05100 Structural Metal Framing

WALLS\AREA B

No.	Condition	Height	Quantity	Man Days
	NO INSULATION IS INCLUDED IN THIS CONDITION PER WALL TYPE SCHEDULE			
41	WALL TYPE 13 - CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET; 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE, ADD 2" THICK FOAM ACOUSTIC TREATMENT APPLIED FULL HIGHT TO WALL SURFACES IN ROOMS 1006A AND 1006B ONLY	12' 0"	148.83 LF	12.65
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET; 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	187.72 LF	15.96
48	WALL TYPE 13 - W/ TILE BACKER EACH SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET; 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	19.42 LF	1.65
			Material & Labor Total:	36,350.37 67.24
			WALLS\AREA B Total:	36,350.37 67.24

WALLS\AREA C

No.	Condition	Height	Quantity	Man Days
14	WALL TYPE 10 CONTINUOUS SEALANT TOP AND BOTTOM EACH SIDE 5/8" GYPSUM WALLBOARD TO UNDERSIDE OF DECK, TAPE AND SPACKLE ALL JOINTS 8" STL, STUD (18 GA @ 12" O.C.	24' 0"	80.29 LF	13.34
22	WALL TYPE 11 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16" O.C. DASHED LINE DENOTES STRUCTURAL STL, TUBE CONCEALED W/ PARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A.) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES	14' 0"	55.35 LF	4.59
29	WALL TYPE 12 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	60.83 LF	5.49
39	WALL TYPE 13 - W/ NO INSULATION NO INSULATION IS INCLUDED IN THIS CONDITION PER WALL TYPE SCHEDULE	13' 0"	160.99 LF	14.69
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET; 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	64.90 LF	5.52
48	WALL TYPE 13 - W/ TILE BACKER EACH SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET; 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	30.81 LF	2.62
			Material & Labor Total:	25,006.01 46.24
			WALLS\AREA C Total:	25,006.01 46.24
			05100 Structural Metal Framing Total:	140,380.96 259.73

06100 Rough Carpentry

WALLS\AREA A

No.	Condition	Height	Quantity	Man Days
8	WALL TYPE 04 - DETAIL 1/A5.3.07	9' 0"	77.00 LF	8.18

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

06100 Rough Carpentry WALLSIAREA A

No.	Condition	Height	Quantity	Man Days	
	1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL				
10	WALL TYPE 06	22' 0"	36.00 LF	1.25	
	RIGID BOARD INSULATION R= 11 VALUE FACE OF TILT-UP PANEL OR 8" CMU WALL 5/8" GYPSUM BOARD, TAPE AND SPACKLE ALL JOINTS 2 1/2" METAL STUD FURRING AT 16" OC 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL, STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD TO 12' HIGH ABOVE FINISHED 7/8" FURRING CHANNEL HORIZONTALLY ABOVE 12'-0" HEIGHT @16" O.C. CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTURE, TOP AND BOTTOM				
13	WALL TYPE 09	22' 0"	140.90 LF	4.89	
	CONTINUOUS SEALANT 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS 8" STL, STUD (18 GA) @12" O.C. 3/4" FIRE PETARDANT TREATED PLYWOOD BD, ATTACHED TO STL, STUD W/COUNTER SUNK SCREWS (EXTEND PLYWOOD TO 12'-0" AFF AT EXHIBIT AREAS)				
21	WALL TYPE 09	24' 0"	33.53 LF	1.16	
22	WALL TYPE 11	14' 0"	294.32 LF	11.92	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16"O.C. DASHED LINE DENOTES STRUCTUPAL STL, TUBE CONCEALED W/I RARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A.) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES				
29	WALL TYPE 12	12' 0"	229.04 LF	15.90	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBORAD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
47	WALL TYPE 11- W/ TILE BACKER	14' 0"	24.00 LF	0.97	
			Material & Labor Total:	22,132.29	44.28
			WALLSIAREA A Total:	22,132.29	44.28

WALLSIAREA B

No.	Condition	Height	Quantity	Man Days	
8	WALL TYPE 04 - DETAIL 1/A5.3.07	9' 0"	69.00 LF	7.33	
	1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL				
22	WALL TYPE 11	14' 0"	47.50 LF	1.92	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16"O.C. DASHED LINE DENOTES STRUCTUPAL STL, TUBE CONCEALED W/I RARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A.) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES				
29	WALL TYPE 12	12' 0"	24.33 LF	1.69	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBORAD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
			Material & Labor Total:	5,250.84	10.94
			WALLSIAREA B Total:	5,250.84	10.94

WALLSIAREA C

No.	Condition	Height	Quantity	Man Days
8	WALL TYPE 04 - DETAIL 1/A5.3.07	9' 0"	41.00 LF	4.36
	1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL			
22	WALL TYPE 11	14' 0"	55.35 LF	2.24
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16"O.C. DASHED LINE DENOTES STRUCTUPAL STL, TUBE CONCEALED W/I RARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A.) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES			
29	WALL TYPE 12	12' 0"	60.83 LF	4.22
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBORAD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

06100 Rough Carpentry WALLS\AREA C

Material & Labor Total: **5,311.52** **10.82**

WALLS\AREA C Total: **5,311.52** **10.82**

06100 Rough Carpentry Total: **32,694.64** **66.04**

07210 Building Insulation CEILING\AREA A

No.	Condition	Height	Quantity	Man Days
70	DETAIL 1/A50201(ACP-1) 2X4 SUSPENDED ACT CEILING 4" MAIN CARRIER STUD ATTACHED TO WALL		1,247.71 SF	0.81
72	(GYP) GYP BD AT 10'-0"TH CEILING HEIGHT W/ INSUL ACOUSTICAL BATT INSULATION OVER CEILING INCLUDING METAL FRAMING		410.39 SF	0.27

Material & Labor Total: **759.85** **1.07**

CEILING\AREA A Total: **759.85** **1.07**

CEILING\AREA B

No.	Condition	Height	Quantity	Man Days
69	(GYP) GYP BD AT 10'-0"TH CEILING HEIGHT W/ INSUL ACOUSTICAL BATT INSULATION OVER CEILING		162.88 SF	0.11
70	DETAIL 1/A50201(ACP-1) 2X4 SUSPENDED ACT CEILING 4" MAIN CARRIER STUD ATTACHED TO WALL		673.97 SF	0.44

Material & Labor Total: **383.50** **0.54**

CEILING\AREA B Total: **383.50** **0.54**

WALLS\AREA A

No.	Condition	Height	Quantity	Man Days
6	WALL TYPE 02(1) 2" THICK FOIL FACED ACOUSTIC RIGID INSULATION, APPLY FULL HEIGHT WITH IMPALING PINS TO MASONRY WALL SURFACES FACING MECHANICAL ROOMS AND WAREHOUSE AREAS ADJACENT TO OFFICES OR OCCUPIED SPACES 5/8" GYPSUM WALLBOARD 6" ABOVE FINISH CEILING, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D	22' 0"	140.00 LF	10.36
7	WALL TYPE 03 RIGID BOARD INSULATION R= 11 VALUE 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O.C. METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDERSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTURE, TOP AND BOTTOM	22' 4"	318.00 LF	37.43
10	WALL TYPE 06 RIGID BOARD INSULATION R= 11 VALUE FACE OF TILT-UP PANEL OR 8" CMU WALL 5/8" GYPSUM BOARD, TAPE AND SPACKLE ALL JOINTS 2 1/2" METAL STUD FURRING AT 16" OC 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD TO 12' HIGH ABOVE FINISHED 7/8" FURRING CHANNEL HORIZONTALLY ABOVE 12'-0" HEIGHT @16" O.C. CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTURE, TOP AND BOTTOM	22' 0"	36.00 LF	4.17
17	WALL TYPE 13	14' 0"	106.76 LF	1.38
18	WALL TYPE 14 - CHASE	12' 0"	16.55 LF	0.37
20	WALL TYPE 03	24' 4"	146.13 LF	18.74
22	WALL TYPE 11 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16" O.C. DASHED LINE DENOTES STRUCTURAL STL, TUBE CONCEALED W/ PARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A.) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES	14' 0"	294.32 LF	3.81
26	WALL TYPE 14 -	14' 0"	26.27 LF	0.34
29	WALL TYPE 12	12' 0"	229.04 LF	2.54

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

07210 Building Insulation

WALLS\AREA A

No.	Condition	Height	Quantity	Man Days	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBORAD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
41	WALL TYPE 13 -	12' 0"	62.75 LF	3.85	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE, ADD 2" THICK FOAM ACOUSTIC TREATMENT APPLIED FULL HIGHT TO WALL SURFACES IN ROOMS 1006A AND 1006B ONLY				
42	WALL TYPE 14 -	12' 0"	39.98 LF	0.44	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE	12' 0"	153.14 LF	1.70	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
47	WALL TYPE 11- W/ TILE BACKER	14' 0"	24.00 LF	0.31	
			Material & Labor Total:	45,366.09	85.45
			WALLS\AREA A Total:	45,366.09	85.45

WALLS\AREA B

No.	Condition	Height	Quantity	Man Days
5	WALL TYPE 01	24' 4"	33.00 LF	4.22
	2 1/2" METAL STUD FURRING AT 16" OC FOIL FACED RIGID BOARD INSULATION WITH R-11 VALUE AT MECHANICAL AND ELECTRICAL ROOMS ADJACENT TO EXTERIOR WALLS WIRE MESH ATTACHED TO FURRING STUDS TO CONTAIN INSULATION			
6	WALL TYPE 02(1)	22' 0"	68.00 LF	5.03
	2" THICK FOIL FACED ACOUSTIC RIGID INSULATION, APPLY FULL HEIGHT WITH IMPALING PINS TO MASONRY WALL SURFACES FACING MECHANICAL ROOMS ANDWAREHOUSE AREAS ADJACENT TO OFFICES OR OCCUPIED SRACES 5/8" GYRSUM WALLBOARD 6" ABOVE FINISH CEILING, TAPE AND SRACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D			
7	WALL TYPE 03	22' 4"	246.00 LF	28.95
	RIGID BOARD INSULATION R= 11 VALUE 5/8" GYRSUM WALLBOAPD, TAPE AND SRACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O.C, METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDERSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTUPE, TOP AND BOTTOM			
20	WALL TYPE 03	24' 4"	107.02 LF	13.72
22	WALL TYPE 11	14' 0"	47.50 LF	0.62
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16"O.C. DASHED LINE DENOTES STRUCTUPAL STL, TUBE CONCEALED W/I PARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A,) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES			
29	WALL TYPE 12	12' 0"	24.33 LF	0.27
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBORAD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
41	WALL TYPE 13 -	12' 0"	148.83 LF	9.13
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE, ADD 2" THICK FOAM ACOUSTIC TREATMENT APPLIED FULL HIGHT TO WALL SURFACES IN ROOMS 1006A AND 1006B ONLY			
43	WALL TYPE 14 - W/ TILE BACKER ONE SIDE	12' 0"	73.88 LF	0.82

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

07210 Building Insulation

WALLSAREA B

No.	Condition	Height	Quantity	Man Days	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
44	WALL TYPE 14 - W/ TILE BACKER EACH SIDE	12' 0"	39.36 LF	0.87	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE	12' 0"	187.72 LF	2.09	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (IS GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
48	WALL TYPE 13 - W/ TILE BACKER EACH SIDE	12' 0"	19.42 LF	0.22	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (IS GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
			Material & Labor Total:	33,738.81	65.94
			WALLSAREA B Total:	33,738.81	65.94

WALLSAREA C

No.	Condition	Height	Quantity	Man Days
7	WALL TYPE 03	22' 4"	105.00 LF	12.36
	RIGID BOARD INSULATION R= 11 VALUE 5/8" GYRSUM WALLBOAPD, TAPE AND SRACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O,C, METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDERSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTUPE, TOP AND BOTTOM			
20	WALL TYPE 03	24' 4"	241.83 LF	31.01
22	WALL TYPE 11	14' 0"	55.35 LF	0.72
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16"O.C. DASHED LINE DENOTES STRUCTUPAL STL, TUBE CONCEALED W/I PARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A,) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES			
29	WALL TYPE 12	12' 0"	60.83 LF	0.68
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBORAD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
42	WALL TYPE 14 -	12' 0"	10.87 LF	0.12
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE	12' 0"	64.90 LF	0.72
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (IS GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
48	WALL TYPE 13 - W/ TILE BACKER EACH SIDE	12' 0"	30.81 LF	0.34
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (IS GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
49	WALL TYPE 14 - W/ TILE BACKER ONE SIDE	12' 0"	15.92 LF	0.35
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

07210 Building Insulation WALLS\AREA C

Material & Labor Total: **21,204.67** **46.30**

WALLS\AREA C Total: **21,204.67** **46.30**

07210 Building Insulation Total: **101,452.92** **199.31**

07920 Joint Sealants CEILING\AREA B

No.	Condition	Height	Quantity	Man Days
65	DETAIL 5/A5201 (GYP) 2-HR RATED GYP BD CEILING STL "J" RUNNER CONTINUOUS, 2-1/2" CH STUD @ 24 OC, 1" FIRE RATED GYP LINER, (2) 1/2" GYP BD FIRE RATED, CONTINUOUS SEALANT		46.76 SF	0.08
73	DETAIL 15/A5201 (GYP) 2-HR RATED GYP BD CEILING STL "J" RUNNER CONTINUOUS, 2-1/2" CH STUD @ 24 OC, 1" FIRE RATED GYP LINER, (2) 1/2" GYP BD FIRE RATED, CONTINUOUS SEALANT		88.40 SF	0.08

Material & Labor Total: **51.06** **0.16**

CEILING\AREA B Total: **51.06** **0.16**

WALLS\AREA A

No.	Condition	Height	Quantity	Man Days
6	WALL TYPE 02(1) 2" THICK FOIL FACED ACOUSTIC RIGID INSULATION, APPLY FULL HEIGHT WITH IMPALING PINS TO MASONRY WALL SURFACES FACING MECHANICAL ROOMS AND WAREHOUSE AREAS ADJACENT TO OFFICES OR OCCUPIED SPACES 5/8" GYPSUM WALLBOARD 6" ABOVE FINISH CEILING, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D	22' 0"	140.00 LF	0.28
7	WALL TYPE 03 RIGID BOARD INSULATION R= 11 VALUE 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O.C, METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDERSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTURE, TOP AND BOTTOM	22' 4"	318.00 LF	1.42
8	WALL TYPE 04 - DETAIL 1/A5.3.07 1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL	9' 0"	77.00 LF	0.31
9	WALL TYPE 05 CONTINUOUS 7/8" FURRING CHANNELS AT 5/8" GYP SUM BOARD TO 6" ABOVE CEILING, TAPE AND SPACKLE ALL JOINTS 7/8" FURRING CHANNELS @ 16" O.C.	12' 0"	11.00 LF	0.04
10	WALL TYPE 06 RIGID BOARD INSULATION R= 11 VALUE FACE OF TILT-UP PANEL OR 8" CMU WALL 5/8" GYPSUM BOARD, TAPE AND SPACKLE ALL JOINTS 2 1/2" METAL STUD FURRING AT 16" OC 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL, STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD TO 12" HIGH ABOVE FINISHED 7/8" FURRING CHANNEL HORIZONTALLY ABOVE 12'-0" HEIGHT @16" O.C. CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTURE, TOP AND BOTTOM	22' 0"	36.00 LF	0.15
11	WALL TYPE 07 - W/ TILE BACKER CONTINUOUS 7/8" FURRING CHANNELS AT BASE WALL BASE AS SCHED, BOTH SIDES FINISH FLOOR AS SCHED, BOTH SIDES WAINSCOTE CERAMIC TILE, REFER TO INTEPIOR TOILET ELEVATIONS FOR SPECIFIC HEIGHTS 5/8" CEMENTITIOUS WALL BOARD AT SURFACES RECEIVING TILE 5/8" GYPSUM WALL BOARD, TAPE AND SPACKLE ALL JOINTS ON NON-TILED SURFACES	12' 0"	32.00 LF	0.06
13	WALL TYPE 09 CONTINUOUS SEALANT 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS 8" STL, STUD (18 GA) @12" O.C. 3/4" FIRE PETARDANT TREATED PLYWOOD BD, ATTACHED TO STL, STUD W/COUNTER SUNK SCREWS (EXTEND PLYWOOD TO 12'-0" AFF AT EXHIBIT AREAS)	22' 0"	140.90 LF	1.14
14	WALL TYPE 10 CONTINUOUS SEALANT TOP AND BOTTOM EACH SIDE 5/8" GYPSUM WALLBOARD TO UNDERSIDE OF DECK, TAPE AND SPACKLE ALLJOINTS 8" STL, STUD (18 GA @ 12" O.C.	24' 0"	22.82 LF	0.18
17	WALL TYPE 13	14' 0"	106.76 LF	0.43
18	WALL TYPE 14 - CHASE	12' 0"	16.55 LF	0.07
20	WALL TYPE 03	24' 4"	146.13 LF	0.65
21	WALL TYPE 09	24' 0"	33.53 LF	0.27
22	WALL TYPE 11	14' 0"	294.32 LF	1.19

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

07920 Joint Sealants

WALLS\AREA A

No.	Condition	Height	Quantity	Man Days	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16" O.C. DASHED LINE DENOTES STRUCTURAL STL, TUBE CONCEALED W/ PARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A,) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES				
23	WALL TYPE 04 (1)	22' 0"	68.01 LF	0.28	
24	WALL TYPE 04	22' 0"	12.92 LF	0.05	
	5/8" GYPSUM BOARD, TARE AND SPACKLE ALL JOINTS 7/8" FURRING CHANNEL AT 16" OC WALL FINISH AS SCHED METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D EXTEND GYPSUM BOARD TO UNDEPSIDE OF ROOF DECK				
26	WALL TYPE 14 -	14' 0"	26.27 LF	0.11	
29	WALL TYPE 12	12' 0"	229.04 LF	0.93	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
39	WALL TYPE 13 - W/ NO INSULATION	13' 0"	33.69 LF	0.14	
	NO INSULATION IS INCLUDED IN THIS CONDITION PER WALL TYPE SCHEDULE				
41	WALL TYPE 13 -	12' 0"	62.75 LF	0.25	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE, ADD 2" THICK FOAM ACOUSTIC TREATMENT APPLIED FULL HEIGHT TO WALL SURFACES IN ROOMS 1006A AND 1006B ONLY				
42	WALL TYPE 14 -	12' 0"	39.98 LF	0.16	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERS ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE	12' 0"	153.14 LF	0.62	
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (18 GA) @ 16" OC, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE				
47	WALL TYPE 11- W/ TILE BACKER	14' 0"	24.00 LF	0.10	
			Material & Labor Total:	2,786.45	8.84
			WALLS\AREA A Total:	2,786.45	8.84

WALLS\AREA B

No.	Condition	Height	Quantity	Man Days
5	WALL TYPE 01	24' 4"	33.00 LF	0.15
	2 1/2" METAL STUD FURRING AT 16" OC FOIL FACED RIGID BOARD INSULATION WITH R-11 VALUE AT MECHANICAL AND ELECTRICAL ROOMS ADJACENT TO EXTERIOR WALLS WIRE MESH ATTACHED TO FURRING STUDS TO CONTAIN INSULATION			
6	WALL TYPE 02(1)	22' 0"	68.00 LF	0.14
	2" THICK FOIL FACED ACOUSTIC RIGID INSULATION, APPLY FULL HEIGHT WITH IMPALING PINS TO MASONRY WALL SURFACES FACING MECHANICAL ROOMS AND WAREHOUSE AREAS ADJACENT TO OFFICES OR OCCUPIED SPACES 5/8" GYPSUM WALLBOARD 6" ABOVE FINISH CEILING, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D			
7	WALL TYPE 03	22' 4"	246.00 LF	1.10
	RIGID BOARD INSULATION R= 11 VALUE 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O.C, METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDEPSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTURE, TOP AND BOTTOM			
8	WALL TYPE 04 - DETAIL 1/A5.3.07	9' 0"	69.00 LF	0.28
	1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL			
9	WALL TYPE 05	12' 0"	70.00 LF	0.28
	CONTINUOUS 7/8" FURRING CHANNELS AT 5/8" GYPSUM BOARD TO 6" ABOVE CEILING, TAPE AND SPACKLE ALL JOINTS 7/8" FURRING CHANNELS @ 16" O.C.			
19	WALL TYPE 15 - 2HR RATED ASSEMBLY	12' 0"	7.69 LF	0.03

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

07920 Joint Sealants

WALLSIAREA B

No.	Condition	Height	Quantity	Man Days
	CONTINUOUS SEALANT EACH SIDE BOTTOM, 3 5/8" STL. STUD @ 16" O.C, 2 LAYEPS OF 5/8" FIRE CODE "C" GYPSUM WALLBOARD PANELS EACH SIDE 2 HR, RATING (UL DES, U411 OR U419)			
20	WALL TYPE 03	24' 4"	107.02 LF	0.48
22	WALL TYPE 11	14' 0"	47.50 LF	0.19
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16"O.C. DASHED LINE DENOTES STRUCTUPAL STL, TUBE CONCEALED W/I PARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A,) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES			
29	WALL TYPE 12	12' 0"	24.33 LF	0.10
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBORAD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
39	WALL TYPE 13 - W/ NO INSULATION	13' 0"	337.98 LF	1.37
	NO INSULATION IS INCLUDED IN THIS CONDITION PER WALL TYPE SCHEDULE			
41	WALL TYPE 13 -	12' 0"	148.83 LF	0.60
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE, ADD 2" THICK FOAM ACOUSTIC TREATMENT APPLIED FULL HIGHT TO WALL SURFACES IN ROOMS 1006A AND 1006B ONLY			
43	WALL TYPE 14 - W/ TILE BACKER ONE SIDE	12' 0"	73.88 LF	0.30
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
44	WALL TYPE 14 - W/ TILE BACKER EACH SIDE	12' 0"	39.36 LF	0.16
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE	12' 0"	187.72 LF	0.76
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (18 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
48	WALL TYPE 13 - W/ TILE BACKER EACH SIDE	12' 0"	19.42 LF	0.08
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (18 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
			Material & Labor Total:	1,895.19 6.01
			WALLSIAREA B Total:	1,895.19 6.01

WALLSIAREA C

No.	Condition	Height	Quantity	Man Days
7	WALL TYPE 03	22' 4"	105.00 LF	0.47
	RIGID BOARD INSULATION R= 11 VALUE 5/8" GYRSUM WALLBOAPD, TAPE AND SRACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O,C, METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDERSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTUPE, TOP AND BOTTOM			
8	WALL TYPE 04 - DETAIL 1/A5.3.07	9' 0"	41.00 LF	0.17
	1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL			
14	WALL TYPE 10	24' 0"	80.29 LF	0.65
	CONTINUOUS SEALANT TOP AND BOTTOM EACH SIDE 5/8" GYPSUM WALLBOARD TO UNDERSIDE OF DECK,TAPE AND SPACKLE ALLJOINTS 8" STL, STUD (18 GA @ 12" O.C.			
20	WALL TYPE 03	24' 4"	241.83 LF	1.08
22	WALL TYPE 11	14' 0"	55.35 LF	0.22

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

07920 Joint Sealants

WALLS\AREA C

No.	Condition	Height	Quantity	Man Days
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16" O.C. DASHED LINE DENOTES STRUCTURAL STL, TUBE CONCEALED W/ PARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A,) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES			
29	WALL TYPE 12	12' 0"	60.83 LF	0.25
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
39	WALL TYPE 13 - W/ NO INSULATION	13' 0"	160.99 LF	0.65
	NO INSULATION IS INCLUDED IN THIS CONDITION PER WALL TYPE SCHEDULE			
42	WALL TYPE 14 -	12' 0"	10.87 LF	0.04
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C. 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERS ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE	12' 0"	64.90 LF	0.26
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET; 1010, MALE TOILET, 8" STL. STUD (18 GA) @ 16" OC, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
48	WALL TYPE 13 - W/ TILE BACKER EACH SIDE	12' 0"	30.81 LF	0.12
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET; 1010, MALE TOILET, 8" STL. STUD (18 GA) @ 16" OC, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
49	WALL TYPE 14 - W/ TILE BACKER ONE SIDE	12' 0"	15.92 LF	0.06
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C. 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERS ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
			Material & Labor Total:	1,254.84 3.98
			WALLS\AREA C Total:	1,254.84 3.98
			07920 Joint Sealants Total:	5,987.54 19.00

08110 Access Doors

CEILING\AREA B

No.	Condition	Height	Quantity	Man Days
61	INSTALLATION OF ACCESS - DETAIL 3/A5201 INSTALLATION OF ACCESS PANEL IN DRYWALL CEILING ONLY	2' 0"	2.00 EA	0.50
			Material & Labor Total:	146.95 0.50
			CEILING\AREA B Total:	146.95 0.50
			08110 Access Doors Total:	146.95 0.50

09221 Non Structural Metal Framing

CEILING\AREA A

No.	Condition	Height	Quantity	Man Days
3	DETAIL 14/A50201 (GYP) GYP BD CEILING ATTACHED TO ROOF JOIST GYP BOARD CEILING ON FURRING ON CARRIER CHANNEL WITH PERIMETER TRIM		1,733.18 SF	20.59
58	"I" DROP SOFFIT GYP BD ON ONE SIDE WITH CORNER BEAD	2' 0"	18.58 LF	0.29
60	(GYP) MR GYPSUM BOARD CEILING @ RESTROOM		633.72 SF	7.12
64	(GYP) GYPSUM BOARD CEILING AT CEILING HEIGHT		881.80 SF	9.91
71	"I" DROP SOFFIT	5' 0"	34.83 LF	0.81

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

09221 Non Structural Metal Framing

CEILING\AREA A

No.	Condition	Height	Quantity	Man Days
72	GYP BD ON EACH SIDE WITH CORNER BEAD (GYP) GYP BD AT 10'-0"TH CEILING HEIGHT W/ INSUL ACOUSTICAL BATT INSULATION OVER CEILING INCLUDING METAL FRAMING		410.39 SF	4.61
			Material & Labor Total:	13,689.46 43.33
			CEILING\AREA A Total:	13,689.46 43.33

CEILING\AREA B

No.	Condition	Height	Quantity	Man Days
3	DETAIL 14/A50201 (GYP) GYP BD CEILING ATTACHED TO ROOF JOIST GYP BOARD CEILING ON FURRING ON CARRIER CHANNEL WITH PERIMETER TRIM		7,736.33 SF	91.91
58	"1" DROP SOFFIT GYP BD ON ONE SIDE WITH CORNER BEAD	2' 0"	18.33 LF	0.29
60	(GYP) MR GYPSUM BORAD CEILING @ RESTROOM		836.44 SF	9.40
62	(DETAIL 1/A4205) "L" 4'-0"W GYPSUM SOFFIT 3'-0"HT X 4'-0" W	3' 0"	14.42 LF	0.56
63	(DETAIL 1/A4205) "L" 8'-0"W GYPSUM SOFFIT 3'-0"HT X 8'-0" W	3' 0"	12.92 LF	0.64
64	(GYP) GYPSUM BORAD CEILING AT CEILING HEIGHT		387.52 SF	4.35
65	DETAIL 5/A5201 (GYP) 2-HR RATED GYP BD CEILING STL "J" RUNNER CONTINUOUS, 2-1/2" CH STUD @ 24 OC, 1" FIRE RATED GYP LINER, (2) 1/2" GYP BD FIRE RATED, CONTINUOUS SEALANT		46.76 SF	4.06
69	(GYP) GYP BD AT 10'-0"TH CEILING HEIGHT W/ INSUL ACOUSTICAL BATT INSULATION OVER CEILING		162.88 SF	1.83
73	DETAIL 15/A5201 (GYP) 2-HR RATED GYP BD CEILING STL "J" RUNNER CONTINUOUS, 2-1/2" CH STUD @ 24 OC, 1" FIRE RATED GYP LINER, (2) 1/2" GYP BD FIRE RATED, CONTINUOUS SEALANT		88.40 SF	7.68
			Material & Labor Total:	35,554.52 120.71
			CEILING\AREA B Total:	35,554.52 120.71

CEILING\AREA C

No.	Condition	Height	Quantity	Man Days
3	DETAIL 14/A50201 (GYP) GYP BD CEILING ATTACHED TO ROOF JOIST GYP BOARD CEILING ON FURRING ON CARRIER CHANNEL WITH PERIMETER TRIM		393.99 SF	4.68
60	(GYP) MR GYPSUM BORAD CEILING @ RESTROOM		186.76 SF	2.10
64	(GYP) GYPSUM BORAD CEILING AT CEILING HEIGHT		289.56 SF	3.25
66	"L" 26"-0"W GYPSUM SOFFIT	3' 0"	33.50 LF	1.22
67	"L" 2'-11"-0"W GYPSUM SOFFIT	3' 0"	10.08 LF	0.34
			Material & Labor Total:	3,798.42 11.59
			CEILING\AREA C Total:	3,798.42 11.59

WALLS\AREA A

No.	Condition	Height	Quantity	Man Days
6	WALL TYPE 02(1) 2" THICK FOIL FACED ACOUSTIC RIGID INSULATION, APPLY FULL HEIGHT WITH IMPALING PINS TO MASONRY WALL SURFACES FACING MECHANICAL ROOMS AND WAREHOUSE AREAS ADJACENT TO OFFICES OR OCCUPIED SPACES 5/8" GYPSUM WALLBOARD 6" ABOVE FINISH CEILING, TAPE AND SCRACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D	22' 0"	140.00 LF	5.44

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

09221 Non Structural Metal Framing

WALLS\AREA A

No.	Condition	Height	Quantity	Man Days
7	WALL TYPE 03 RIGID BOARD INSULATION R= 11 VALUE 5/8" GYRSUM WALLBOAPD, TAPE AND SRACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O,C, METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDERSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTUPE, TOP AND BOTTOM	22' 4"	318.00 LF	23.35
8	WALL TYPE 04 - DETAIL 1/A5.3.07 1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL	9' 0"	77.00 LF	2.99
9	WALL TYPE 05 CONTINUOUS 7/8" FURRING CHANNELS AT 5/8" GYP SUM BOARD TO 6" ABOVE CEILING, TAPE AND SRACKLE ALL JOINTS 7/8" FURRING CHANNELS @ 16"O.C.	12' 0"	11.00 LF	0.86
10	WALL TYPE 06 RIGID BOARD INSULATION R= 11 VALUE FACE OF TILT-UP PANEL OR 8" CMU WALL 5/8" GYPSUM BOARD, TAPE AND SPACKLE ALL JOINTS 2 1/2" METAL STUD FURRING AT 16" OC 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL, STUD W/COUNTEPSUNK SCREWS (EXTEND PLYWOOD TO 12' HIGH ABOVE FINISHED 7/8" FURRING CHANNEL HORIZONTALLY ABOVE 12'-0" HEIGHT @16" O,C. CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTURE, TOP AND BOTTOM	22' 0"	36.00 LF	2.89
11	WALL TYPE 07 - W/ TILE BACKER CONTINUOUS 7/8" FURRING CHANNELS AT BASE WALL BASE AS SCHED, BOTH SIDES FINISH FLOOR AS SCHED, BOTH SIDES WAINSCOTE CERAMIC TILE, REFER TO INTEPIOR TOILET ELEVATIONS FOR SPECIFIC HEIGHTS 5/8" CEMENTITIOUS WALL BOARD AT SURFACES RECEIVING TILE 5/8" GYPSUM WALL BOARD, TAPE AND SPACKLE ALL JOINTS ON NON-TILED SURFACES	12' 0"	32.00 LF	1.24
13	WALL TYPE 09 CONTINUOUS SEALANT 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS 8" STL, STUD (8 GA) @12" O,C. 3/4" FIRE PETARDANT TREATED PLYWOOD BD, ATTACHED TO STL, STUD W/COUNTER SUNK SCREWS (EXTEND PLYWOOD TO 12'-0" AFF AT EXHIBIT AREAS)	22' 0"	140.90 LF	5.48
18	WALL TYPE 14 - CHASE	12' 0"	16.55 LF	2.74
20	WALL TYPE 03	24' 4"	146.13 LF	11.49
21	WALL TYPE 09	24' 0"	33.53 LF	1.30
23	WALL TYPE 04 (1)	22' 0"	68.01 LF	4.85
24	WALL TYPE 04 5/8" GYRSUM BOARD, TARE AND SPACKLE ALL JOINTS 7/8" FURRING CHANNEL AT 16" OC WALL FINISH AS SCHED METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D EXTEND GYRSUM BOARD TO UNDEPSIDE OF ROOF DECK	22' 0"	12.92 LF	0.92
26	WALL TYPE 14 -	14' 0"	26.27 LF	1.23
42	WALL TYPE 14 - CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	39.98 LF	1.66

Material & Labor Total: 33,180.07 66.45

WALLS\AREA A Total: 33,180.07 66.45

WALLS\AREA B

No.	Condition	Height	Quantity	Man Days
5	WALL TYPE 01 2 1/2" METAL STUD FURRING AT 16" OC FOIL FACED RIGID BOARD INSULATION WITH R-11 VALUE AT MECHANICAL AND ELECTRICAL ROOMS ADJACENT TO EXTERIOR WALLS WIRE MESH ATTACHED TO FURRING STUDS TO CONTAIN INSULATION	24' 4"	33.00 LF	2.59
6	WALL TYPE 02(1) 2" THICK FOIL FACED ACOUSTIC RIGID INSULATION, APPLY FULL HEIGHT WITH IMPALING PINS TO MASONRY WALL SURFACES FACING MECHANICAL ROOMS ANDWAREHOUSE AREAS ADJACENT TO OFFICES OR OCCUPIED SRACES 5/8" GYRSUM WALLBOARD 6" ABOVE FINISH CEILING, TAPE AND SRACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D	22' 0"	68.00 LF	2.64
7	WALL TYPE 03 RIGID BOARD INSULATION R= 11 VALUE 5/8" GYRSUM WALLBOAPD, TAPE AND SRACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O,C, METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDERSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTUPE, TOP AND BOTTOM	22' 4"	246.00 LF	18.07
8	WALL TYPE 04 - DETAIL 1/A5.3.07 1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL	9' 0"	69.00 LF	2.68
9	WALL TYPE 05 CONTINUOUS 7/8" FURRING CHANNELS AT 5/8" GYP SUM BOARD TO 6" ABOVE CEILING, TAPE AND SRACKLE ALL JOINTS 7/8" FURRING CHANNELS @ 16"O.C.	12' 0"	70.00 LF	5.44

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

09221 Non Structural Metal Framing

WALLSIAREA B

No.	Condition	Height	Quantity	Man Days
19	WALL TYPE 15 - 2HR RATED ASSEMBLY CONTINUOUS SEALANT EACH SIDE BOTTOM, 3 5/8" STL. STUD @ 16" O.C, 2 LAYEPS OF 5/8" FIRE CODE "C" GYPSUM WALLBOARD PANELS EACH SIDE 2 HR, RATING (UL DES, U411 OR U419)	12' 0"	7.69 LF	0.32
20	WALL TYPE 03	24' 4"	107.02 LF	8.41
44	WALL TYPE 14 - W/ TILE BACKER EACH SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	39.36 LF	3.26
Material & Labor Total:			22,876.11	43.43
WALLSIAREA B Total:			22,876.11	43.43

WALLSIAREA C

No.	Condition	Height	Quantity	Man Days
7	WALL TYPE 03 RIGID BOARD INSULATION R= 11 VALUE 5/8" GYRSUM WALLBOAPD, TAPE AND SRACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O,C, METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDERSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTUPE, TOP AND BOTTOM	22' 4"	105.00 LF	7.71
8	WALL TYPE 04 - DETAIL 1/A5.3.07 1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL	9' 0"	41.00 LF	1.59
20	WALL TYPE 03	24' 4"	241.83 LF	19.01
42	WALL TYPE 14 - CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	10.87 LF	0.45
Material & Labor Total:			16,706.67	28.77
WALLSIAREA C Total:			16,706.67	28.77

09221 Non Structural Metal Framing Total: 125,805.24 314.27

09290 Drywall

CEILINGIAREA A

No.	Condition	Height	Quantity	Man Days
3	DETAIL 14/A50201 (GYP) GYP BD CEILING ATTACHED TO ROOF JOIST GYP BOARD CEILING ON FURRING ON CARRIER CHANNEL WITH PERIMETER TRIM		1,733.18 SF	9.79
58	"I" DROP SOFFIT GYP BD ON ONE SIDE WITH CORNER BEAD	2' 0"	18.58 LF	0.18
60	(GYP) MR GYPSUM BORAD CEILING @ RESTROOM		633.72 SF	2.85
64	(GYP) GYPSUM BORAD CEILING AT CEILING HEIGHT		881.80 SF	3.97
71	"I" DROP SOFFIT GYP BD ON EACH SIDE WITH CORNER BEAD	5' 0"	34.83 LF	1.53
72	(GYP) GYP BD AT 10'-0"TH CEILING HEIGHT W/ INSUL ACOUSTICAL BATT INSULATION OVER CEILING INCLUDING METAL FRAMING		410.39 SF	3.69
Material & Labor Total:			7,000.91	22.01
CEILINGIAREA A Total:			7,000.91	22.01

CEILINGIAREA B

No.	Condition	Height	Quantity	Man Days
3	DETAIL 14/A50201 (GYP) GYP BD CEILING ATTACHED TO ROOF JOIST GYP BOARD CEILING ON FURRING ON CARRIER CHANNEL WITH PERIMETER TRIM		7,736.33 SF	43.70
58	"I" DROP SOFFIT	2' 0"	18.33 LF	0.18

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

09290 Drywall
CEILING\AREA B

No.	Condition	Height	Quantity	Man Days
	GYP BD ON ONE SIDE WITH CORNER BEAD			
60	(GYP) MR GYPSUM BORAD CEILING @ RESTROOM		836.44 SF	3.76
62	(DETAIL 1/A4205) "L" 4'-0"W GYPSUM SOFFIT 3'-0"HT X 4'-0" W	3' 0"	14.42 LF	0.43
63	(DETAIL 1/A4205) "L" 8'-0"W GYPSUM SOFFIT 3'-0"HT X 8'-0" W	3' 0"	12.92 LF	0.53
64	(GYP) GYPSUM BORAD CEILING AT CEILING HEIGHT		387.52 SF	1.74
65	DETAIL 5/A5201 (GYP) 2-HR RATED GYP BD CEILING		46.76 SF	0.42
	STL "J" RUNNER CONTINUOUS, 2-1/2" CH STUD @ 24 OC, 1" FIRE RATED GYP LINER, (2) 1/2" GYP BD FIRE RATED, CONTINUOUS SEALANT			
69	(GYP) GYP BD AT 10'-0"TH CEILING HEIGHT W/ INSUL		162.88 SF	0.73
	ACOUSTICAL BATT INSULATION OVER CEILING			
73	DETAIL 15/A5201 (GYP) 2-HR RATED GYP BD CEILING		88.40 SF	0.40
	STL "J" RUNNER CONTINUOUS, 2-1/2" CH STUD @ 24 OC, 1" FIRE RATED GYP LINER, (2) 1/2" GYP BD FIRE RATED, CONTINUOUS SEALANT			
			Material & Labor Total:	16,296.54
				51.90
			CEILING\AREA B Total:	16,296.54
				51.90

CEILING\AREA C

No.	Condition	Height	Quantity	Man Days
3	DETAIL 14/A50201 (GYP) GYP BD CEILING ATTACHED TO ROOF JOIST		393.99 SF	2.23
	GYP BOARD CEILING ON FURRING ON CARRIER CHANNEL WITH PERIMETER TRIM			
60	(GYP) MR GYPSUM BORAD CEILING @ RESTROOM		186.76 SF	0.84
64	(GYP) GYPSUM BORAD CEILING AT CEILING HEIGHT		289.56 SF	1.30
66	"L" 26"-0"W GYPSUM SOFFIT	3' 0"	33.50 LF	0.80
67	"L" 2'-11"-0"W GYPSUM SOFFIT	3' 0"	10.08 LF	0.22
			Material & Labor Total:	1,725.80
				5.39
			CEILING\AREA C Total:	1,725.80
				5.39

WALLS\AREA A

No.	Condition	Height	Quantity	Man Days
6	WALL TYPE 02(1)	22' 0"	140.00 LF	6.62
	2" THICK FOIL FACED ACOUSTIC RIGID INSULATION, APPLY FULL HEIGHT WITH IMPALING PINS TO MASONRY WALL SURFACES FACING MECHANICAL ROOMS AND WAREHOUSE AREAS ADJACENT TO OFFICES OR OCCUPIED SPACES			
	5/8" GYPSUM WALLBOARD 6" ABOVE FINISH CEILING, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D			
7	WALL TYPE 03	22' 4"	318.00 LF	27.96
	RIGID BOARD INSULATION R= 11 VALUE 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O.C, METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDERSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTURE, TOP AND BOTTOM			
8	WALL TYPE 04 - DETAIL 1/A5.3.07	9' 0"	77.00 LF	6.01
	1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL			
9	WALL TYPE 05	12' 0"	11.00 LF	1.04
	CONTINUOUS 7/8" FURRING CHANNELS AT 5/8" GYP SUM BOARD TO 6" ABOVE CEILING, TAPE AND SPACKLE ALL JOINTS 7/8" FURRING CHANNELS @ 16" O.C.			
10	WALL TYPE 06	22' 0"	36.00 LF	3.12
	RIGID BOARD INSULATION R= 11 VALUE FACE OF TILT-UP PANEL OR 8" CMU WALL 5/8" GYPSUM BOARD, TAPE AND SPACKLE ALL JOINTS 2 1/2" METAL STUD FURRING AT 16" OC 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD TO 12" HIGH ABOVE FINISHED 7/8" FURRING CHANNEL HORIZONTALLY ABOVE 12'-0" HEIGHT @16" O.C. CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTURE, TOP AND BOTTOM			

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

09290 Drywall WALLS/AREA A

No.	Condition	Height	Quantity	Man Days
11	WALL TYPE 07 - W/ TILE BACKER CONTINUOUS 7/8" FURRING CHANNELS AT BASE WALL BASE AS SCHED, BOTH SIDES FINISH FLOOR AS SCHED, BOTH SIDES WAINSCOTE CERAMIC TILE, REFER TO INTERIOR TOILET ELEVATIONS FOR SPECIFIC HEIGHTS 5/8" CEMENTITIOUS WALL BOARD AT SURFACES RECEIVING TILE 5/8" GYPSUM WALL BOARD, TAPE AND SPACKLE ALL JOINTS ON NON-TILED SURFACES	12' 0"	32.00 LF	1.66
13	WALL TYPE 09 CONTINUOUS SEALANT 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS 8" STL, STUD (18 GA) @12" O.C. 3/4" FIRE PETARDANT TREATED PLYWOOD BD, ATTACHED TO STL, STUD W/COUNTER SUNK SCREWS (EXTEND PLYWOOD TO 12'-0" AFF AT EXHIBIT AREAS)	22' 0"	140.90 LF	24.41
14	WALL TYPE 10 CONTINUOUS SEALANT TOP AND BOTTOM EACH SIDE 5/8" GYPSUM WALLBOARD TO UNDERSIDE OF DECK, TAPE AND SPACKLE ALL JOINTS 8" STL, STUD (18 GA @ 12" O.C.	24' 0"	22.82 LF	4.31
17	WALL TYPE 13	14' 0"	106.76 LF	10.14
18	WALL TYPE 14 - CHASE	12' 0"	16.55 LF	3.80
20	WALL TYPE 03	24' 4"	146.13 LF	14.00
21	WALL TYPE 09	24' 0"	33.53 LF	6.34
22	WALL TYPE 11 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16" O.C. DASHED LINE DENOTES STRUCTUPAL STL, TUBE CONCEALED W/I PARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A,) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES	14' 0"	294.32 LF	33.74
23	WALL TYPE 04 (1)	22' 0"	68.01 LF	5.89
24	WALL TYPE 04 5/8" GYRSUM BOARD, TARE AND SPACKLE ALL JOINTS 7/8" FURRING CHANNEL AT 16" OC WALL FINISH AS SCHED METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D EXTEND GYRSUM BOARD TO UNDEPSIDE OF ROOF DECK	22' 0"	12.92 LF	1.12
25	CORNER GUARDS	8' 0"	15.00 EA	0.18
26	WALL TYPE 14 -	14' 0"	26.27 LF	3.01
29	WALL TYPE 12 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBORAD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	229.04 LF	22.65
30	16'X8' Opening backout	8' 0"	1.00 EA	0.23
31	8'X8' Opening backout	8' 0"	1.00 EA	0.02
32	5'X6' Opening backout	6' 0"	5.00 EA	0.09
33	7'X8' Opening backout	8' 0"	1.00 EA	0.15
38	5'X6' Opening backout	6' 0"	3.00 EA	0.39
39	WALL TYPE 13 - W/ NO INSULATION NO INSULATION IS INCLUDED IN THIS CONDITION PER WALL TYPE SCHEDULE	13' 0"	33.69 LF	3.20
40	11'X8' Opening backout	8' 0"	1.00 EA	0.19
41	WALL TYPE 13 - CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE, ADD 2" THICK FOAM ACOUSTIC TREATMENT APPLIED FULL HIGHT TO WALL SURFACES IN ROOMS 1006A AND 1006B ONLY	12' 0"	62.75 LF	5.96
42	WALL TYPE 14 - CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	39.98 LF	3.95
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	153.14 LF	16.29
47	WALL TYPE 11- W/ TILE BACKER	14' 0"	24.00 LF	2.76
50	1/2" VERT. REVEAL CHANNEL SCREED - DETAIL B/A5307 REVEAL CHANNEL SCREED TO BE INSTALL AT TILT WALL JOINTS FROM AFF TO UNDRESIDE OF DECK	24' 0"	17.00 EA	2.03

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

09290 Drywall WALLSAREA A

No.	Condition	Height	Quantity	Man Days
51	CORNER BEAD VERT. 12'-0"HT - DETAIL 34/A5.3.04	12' 0"	22.00 EA	0.51
52	CORNER BEAD VERT. 24'-0"HT - DETAIL 34/A5.3.04	24' 0"	6.00 EA	0.28
			Material & Labor Total:	72,881.58
			WALLSAREA A Total:	212.01

WALLSAREA B

No.	Condition	Height	Quantity	Man Days
5	WALL TYPE 01 2 1/2" METAL STUD FURRING AT 16" OC FOIL FACED RIGID BOARD INSULATION WITH R-11 VALUE AT MECHANICAL AND ELECTRICAL ROOMS ADJACENT TO EXTERIOR WALLS WIRE MESH ATTACHED TO FURRING STUDS TO CONTAIN INSULATION	24' 4"	33.00 LF	3.16
6	WALL TYPE 02(1) 2" THICK FOIL FACED ACOUSTIC RIGID INSULATION, APPLY FULL HEIGHT WITH IMPALING PINS TO MASONRY WALL SURFACES FACING MECHANICAL ROOMS AND WAREHOUSE AREAS ADJACENT TO OFFICES OR OCCUPIED SPACES 5/8" GYPSUM WALLBOARD 6" ABOVE FINISH CEILING, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D	22' 0"	68.00 LF	3.21
7	WALL TYPE 03 RIGID BOARD INSULATION R= 11 VALUE 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O.C, METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDERSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTURE, TOP AND BOTTOM	22' 4"	246.00 LF	21.63
8	WALL TYPE 04 - DETAIL 1/A5.3.07 1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL	9' 0"	69.00 LF	5.38
9	WALL TYPE 05 CONTINUOUS 7/8" FURRING CHANNELS AT 5/8" GYP SUM BOARD TO 6" ABOVE CEILING, TAPE AND SPACKLE ALL JOINTS 7/8" FURRING CHANNELS @ 16"O.C.	12' 0"	70.00 LF	6.62
19	WALL TYPE 15 - 2HR RATED ASSEMBLY CONTINUOUS SEALANT EACH SIDE BOTTOM, 3 5/8" STL. STUD @ 16" O.C, 2 LAYERS OF 5/8" FIRE CODE "C" GYPSUM WALLBOARD PANELS EACH SIDE 2 HR, RATING (UL DES, U411 OR U419)	12' 0"	7.69 LF	1.18
20	WALL TYPE 03	24' 4"	107.02 LF	10.25
22	WALL TYPE 11 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16"O.C. DASHED LINE DENOTES STRUCTURAL STL, TUBE CONCEALED W/ PARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A,) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES	14' 0"	47.50 LF	5.44
25	CORNER GUARDS	8' 0"	5.00 EA	0.06
29	WALL TYPE 12 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	24.33 LF	2.41
39	WALL TYPE 13 - W/ NO INSULATION NO INSULATION IS INCLUDED IN THIS CONDITION PER WALL TYPE SCHEDULE	13' 0"	337.98 LF	32.09
41	WALL TYPE 13 - CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO; 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET; 1010, MALE TOILET, 8" STL. STUD (16 GA) @ 16" OC, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE, ADD 2" THICK FOAM ACOUSTIC TREATMENT APPLIED FULL HEIGHT TO WALL SURFACES IN ROOMS 1006A AND 1006B ONLY	12' 0"	148.83 LF	14.13
43	WALL TYPE 14 - W/ TILE BACKER ONE SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERS ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	73.88 LF	10.78
44	WALL TYPE 14 - W/ TILE BACKER EACH SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERS ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	39.36 LF	6.03

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

**09290 Drywall
WALLSAREA B**

No.	Condition	Height	Quantity	Man Days
45	3'X6' Opening backout	6' 0"	1.00 EA	0.08
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (IS GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	187.72 LF	19.97
48	WALL TYPE 13 - W/ TILE BACKER EACH SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (IS GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	19.42 LF	1.96
50	1/2" VERT. REVEAL CHANNEL SCREED - DETAIL B/A5307 REVEAL CHANNEL SCREED TO BE INSTALL AT TILT WALL JOINTS FROM AFF TO UNDRESIDE OF DECK	24' 0"	14.00 EA	1.67
51	CORNER BEAD VERT. 12'-0"HT - DETAIL 34/A5.3.04	12' 0"	39.00 EA	0.91
52	CORNER BEAD VERT. 24'-0"HT - DETAIL 34/A5.3.04	24' 0"	3.00 EA	0.14
Material & Labor Total:				51,614.38 147.10
WALLSAREA B Total:				51,614.38 147.10

WALLSAREA C

No.	Condition	Height	Quantity	Man Days
7	WALL TYPE 03 RIGID BOARD INSULATION R= 11 VALUE 5/8" GYRSUM WALLBOAPD, TAPE AND SRACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS) 2 1/2" METAL STUD FURRING AT 16" O.C, METAL FURRING CHANNEL BETWEEN VERTICAL FURRING AS FIRE BLOCK WHERE REQ'D UNDERSIDE OF METAL ROOF DECK CONTINUOUS SEALANT CONT. RUNNER SECURED TO STRUCTUPE, TOP AND BOTTOM	22' 4"	105.00 LF	9.23
8	WALL TYPE 04 - DETAIL 1/A5.3.07 1X WOOD FURRING, 5/8" SPECIAL REVEAL MOLDING SIMILAR TO FRY REGLET #1054 OR EQUAL	9' 0"	41.00 LF	3.20
14	WALL TYPE 10 CONTINUOUS SEALANT TOP AND BOTTOM EACH SIDE 5/8" GYPSUM WALLBOARD TO UNDERSIDE OF DECK,TAPE AND SPACKLE ALLJOINTS 8" STL, STUD (18 GA @ 12" O.C.	24' 0"	80.29 LF	15.17
20	WALL TYPE 03	24' 4"	241.83 LF	23.17
22	WALL TYPE 11 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBOARD, TARE AND SPACKLE ALL JOINTS 8" STL. STUD (18 GA) @ 16"O.C. DASHED LINE DENOTES STRUCTUPAL STL, TUBE CONCEALED W/I PARTITION, SEE STRUCT. DWGS FOR LOCATION AND SIZE 3/4" FIRE RETARDANT TREATED PLYWOOD BD. ATTACHED TO STL. STUD W/COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXHIBIT (AREAS) (6" SOUND ATTENUATION BLANKET ONLY AT ROOM 1048A.) TOP OF PARTITION, CORNER BEADS TYP. ON ALL SIDES	14' 0"	55.35 LF	6.34
25	CORNER GUARDS	8' 0"	2.00 EA	0.02
29	WALL TYPE 12 CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 5/8" GYPSUM WALLBORAD TAPE AND SPACKLE ALL JOINTS, 8" STL STUD (18 GA) @ 12" OC, 6" SOUND ATTENUATION BLANKET, 3/4" FIRE RETARDANT TREATED PLYWOOD BD ATTACHED TO STL STUD W/ COUNTERSUNK SCREWS (EXTEND PLYWOOD FULL HEIGHT AT EXIBIT AREAS), CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	60.83 LF	6.01
31	8'X8' Opening backout	8' 0"	2.00 EA	0.03
39	WALL TYPE 13 - W/ NO INSULATION NO INSULATION IS INCLUDED IN THIS CONDITION PER WALL TYPE SCHEDULE	13' 0"	160.99 LF	15.28
42	WALL TYPE 14 - CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	10.87 LF	1.07
46	WALL TYPE 13 - W/ TILE BACKER ONE SIDE CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (IS GA) @ 16" OC, 5/8" GYPSUM WALLBOAPD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE	12' 0"	64.90 LF	6.91
48	WALL TYPE 13 - W/ TILE BACKER EACH SIDE	12' 0"	30.81 LF	3.11

Bid Summary

Children's Reading Center & Museum

Bid No. 5 - Job No. 60025276

**09290 Drywall
WALLS\AREA C**

No.	Condition	Height	Quantity	Man Days
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 6" SOUND ATTENUATION BLANKET AT PERIMETER PARTITIONS IN ROOMS 1006B, SINGING STUDIO; 1006A REG. STUDIO: 1037, FEMALE TOILET; 1009, FEMALE TOILET; 1040 MALE TOILET: 1010, MALE TOILET, 8" STL. STUD (IS GA) @ 16" OC, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILE WALL SURFACES AT TOILETS AND SHOWERS, CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
49	WALL TYPE 14 - W/ TILE BACKER ONE SIDE	12' 0"	15.92 LF	3.10
	CONTINUOUS SEALANT EACH SIDE BOTTOM ONLY, 3 1/2" ACOUSTIC BATT INSULATION IN DEMISING PARTITIONS BETWEEN OFFICE SPACES AND AROUND PRIVATE TOILETS, 3 5/8" STL. STUD @ 16" O.C, 5/8" GYPSUM WALLBOARD, TAPE AND SPACKLE ALL JOINTS (USE 1/2" CEMENTITIOUS BOARD IN SUBSTITUTION UNDER TILEWALL SURFACES @ TOILETS & SHOWERT ONLY) CORNER BEAD AT TOP OF WALL TAPE AND SPACKLE			
50	1/2" VERT. REVEAL CHANNEL SCREED - DETAIL B/A5307	24' 0"	8.00 EA	0.95
	REVEAL CHANNEL SCREED TO BE INSTALL AT TILT WALL JOINTS FROM AFF TO UNDRESIDE OF DECK			
51	CORNER BEAD VERT. 12'-0"HT - DETAIL 34/A5.3.04	12' 0"	21.00 EA	0.49
Material & Labor Total:				32,687.21 94.10
WALLS\AREA C Total:				32,687.21 94.10
09290 Drywall Total:				182,206.42 532.51

Additional Markups

Description	%	Total
Bonding	1.00%	6,173.18
Grand Total:		\$617,317.85 1,391.37